

Cordless Grass Trimmer UR012G



As powerful as 40mL petrol grass trimmer



Max Output **2.0** kW









Run Time (BL4050F x2)*

Metal blade

High Med Low 85 / 135 / 249 min

Nylon cutting head

High Med Low 22 / 42 / 106 min

*on a single full battery charge / No load

High power and lar 40mL class engine of

Compatible with a variety of blades

Metal blade	ø305mm	
Plastic blade	ø305mm	
TCT saw blade	ø255mm	
Chisel blade (A specially designed protector is necessary.)	ø255mm	
Nylon cutting head (The cutting cord is ø2.7mm quiet type.)	ø480mm	
Shredder blade (A specially designed protector is necessary.)	ø270mm	

Chisel blade 225 set MG

For brush and thin tree trunks and new growth. Not available in some countries due to local regulation

Part No. 199872-9

Protector 225 set MG





Shredder blade 270 set MG

for thick grass, scrub and vines Part No. 199874-5

Protector set MG Part No. 199875-3







High water-resistance allows to operate the machine even if it is wet with water.



eXtreme Protection Technology

Enhanced Dust and Drip-proof Performance ensure reliable operation even under bad weather



ge cutting width of 480mm similar to grass trimmers



Main power button

Reverse button





Reverse switch for clearing entangled weeds and grass from cutting head

Low noise level

96 or lower dB(A)
with ø480mm nylon cutting head

Max Output **2.0** kW



Rigid ø28mm shaft pipe

is used for heavy-duty operation using Chisel blades or Shredder blades.

The vertical center line of the handle bar always stays aligned with that of user



- Enabling user to work with less fatigue even in long continuous operation.
- Allowing for a wider swing.



Rear end mounted motor


Makes the tool weight balance similar to engine grass trimmers, enabling user to easily lift up the saw head for ridge weed removal, etc.



ADT

Automatic torque Drive Technology


Automatically changes the cutting speed according to grass density.



AFT

Active Feedback sensing Technology

Torque limiter turns the motor off if the tool is suddenly forced to lock



Time

Accessories

Chisel blade

Part No. 199872-9 Blade dia.: 225mm



Protector 225 set MG

Part No. 199873-7



Part No. 197296-3

Ref.: ECO 4L

Cord/Line: 2.0mm x3m



Part No. 199884-2 Cord/Line: 2.7mm Ref.: 105-M10L





Protector set MG

Part No. 199875-3





Trimmer head

Part No. 196324-1 Cord/Line: 2.4mm x3.6m Ref.: UN-74L

Part No. 198266-5 Cord/Line: 2.4mm x6m Ref · UN-72I









Part No. 191D93-3

Cord/Line: 2.4mm

Ref.: 121-M10L



Part No. 191D89-4

Cord/Line: 2.0mm x4m

Part No. 191D91-9

Cord/Line: 2.4mm x3m Ref · 96-M10I

Ref.: 96-M10L



Part No. 198893-8 (EU)

Cord/Line: 2.0mm x3m

Ref.: 95-M10L

Four-leaf Spiral Nylon cord



dieen		
Size	Part No.	
2.0mmx15m	197472-9	
2.0mmx30m	197473-7	
2.0mmx160m	197474-5	
2.0mmx280m	197475-3	

Orange		
Size	Part No.	
2.4mmx15m	198501-1	
2.4mmx30m	198502-9	
2.4mmx120m	198503-7	
2.4mmx180m	198504-5	

Size Part No. 2.7mmx15m E-01828 2.7mmx30m E-01834 2.7mmx180m E-01840

Protection guard for brush cutting blades

Part No. 191B54-1



Brushcutter blade

Blade dia	2-tooth blade	3-tooth blade	4-tooth blade
255mm	198345-9	195299-1	196895-8
305mm	195624-6	195300-2	-

Plastic blade

Cutting width	Plastic blade Set	Replacement plastic blade
255mm	198383-1	198426-9
305mm	199868-0	199870-3

Shoulder strap assembly

Comfort Part No.122A37-4





Charging Time

40 Vitarion	DC40RA Fast Charging	DC40RC
BL4020 2.0Ah	22 min	30 min
BL4025 2.5Ah	28 _{min}	38 min
BL4040 4.0Ah	45 min	67 min
*1 BL4050F 5.0Ah	50 min	85 min

^{*1} Recommended battery

Cordless Grass Trimmer

UR012G

Variable Speed
Brake
Reversing
Electronic 3-Spe
Constant Speed
Soft Start

(Cutting	Width	
	Na I aaa		/DI

No Load Speed (RPM) Spindle Size Sound Pressure Level

Sound Power Level

Vibration Level

Metal Blade: 305 mm (12") Chisel Blade: 225 mm (8-7/8")

Nylon Cutting Head: 480 mm (18-7/8") Shredder Blade: 270 mm (10-5/8") Plastic Blade: 305 mm (12") Metal Blade (3/2/1): 0 - 6,800/0 - 5,000/0 - 3,500 Nylon Cutting Head (3/2/1): 0 - 5,000/0 - 4,200/0 - 3,500

M10 x 1.25 LH 4-Tooth Blade: 84.3 dB(A) / Plastic Blade: 82.9 dB(A) / Nylon Cutting Head: 79.9 dB(A)

4-Tooth Blade: 97.9 dB(A) / Plastic Blade: 92.4 dB(A) / Nylon Cutting Head: 91.6 dB(A)

Heddi 31.0 doj/... Left / Right: 2.5 / 2.5 m/s² or less w/ BL4050F:1,829 x 680 x 590 mm (72 x 26-3/4 x 23-1/4") 8.0 - 9.3 kg (17.6 - 20.5 lbs.) Dimensions (L x W x H) Net Weight

Standard Equipment: Safety Goggles, Metal Blade / Nylon Cutting Head / Plastic Blade (country-specific), Blade Cover (for the product with metal blade), Accessory Bag, Hex Wrench, Box Wrench, Shoulder Belt, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Corporation