



Electric Lawn Mower

ELM3320 330 mm (13") ELM3720 370 mm (14-1/2")

ELM4120 / ELM4121 410 mm (16-1/8")

ELM4620 / ELM4621 460 mm (18-1/8")

New AC Lawn Mower series



Plastic Deck

Compact & Lightweight

ELM3320 (330mm)
2 in 1

ELM3720 (370mm)
2 in 1

ELM4120 (410mm)
2 in 1



Steel Deck

Heavy duty

ELM4121 (410mm)
3 in 1

ELM4620 (460mm)
4 in 1

ELM4621 (460mm)
4 in 1
Self-Propelled



The Redesigned Lawn Mower Series for ease of use

Plastic Deck

ELM3320 2 in 1



330mm



ELM3720 2 in 1



370mm



ELM4120 2 in 1



410mm



Steel Deck

ELM4121 3 in 1



410mm



ELM4620 4 in 1



460mm



ELM4621 4 in 1



460mm



Cutting	Collecting	Mulching	Side-discharging	Self-Propelled (single speed 3.6km/h)	Recommended mowing area
---------	------------	----------	------------------	---------------------------------------	-------------------------

Single-lever cutting height adjustment



Side-discharging (ELM4620 / ELM4621)



Accessories

Rotary lawn mower blade



Photo: YA00000741

Model No.	Size	Part No.
ELM3320	330	YA00000745
ELM3720	370	YA00000746
ELM4120	410	YA00000747
ELM4121	410	YA00000738
ELM4620	460	YA00000741
ELM4621	460	YA00000741

Electric Lawn Mower ELM3320 330 mm (13") ELM3720 370 mm (14-1/2") ELM4120/ELM4121 410 mm (16-1/8") ELM4620/ELM4621 460 mm (18-1/8")

	ELM3320	ELM3720	ELM4120	ELM4121	ELM4620	ELM4621
Continuous rating input	1,200W	1,400W	1,600W	1,600W	1,800W	1,800W
Motor	Universal	Universal	Universal	Universal	Induction	Induction
Cutting Width	330 mm (13")	370 mm (14-1/2")	410 mm (16-1/8")	410 mm (16-1/8")	460 mm (18-1/8")	460 mm (18-1/8")
Cutting Height	20 - 55 mm (13/16" - 2-3/16")	20 - 55 mm (13/16" - 2-3/16")	20 - 75 mm (13/16" - 2-15/16")	20 - 75 mm (13/16" - 2-15/16")	20 - 75 mm (13/16" - 2-15/16")	20 - 75 mm (13/16" - 2-15/16")
No Load Speed (RPM)	3,400	3,400	3,400	3,400	2,950	2,950
Recommended mowing area up to	400 m ²	500 m ²	600 m ²	600 m ²	800 m ²	1,000 m ²
Grass box capacity	30 L	40 L	45 L	45 L	60 L	60 L
Wheel Size Front / Rear:	139 / 178 mm (5-1/2" / 7")	139 / 178 mm (5-1/2" / 7")	156 / 200 mm (6-1/8" / 7-7/8")	156 / 200 mm (6-1/8" / 7-7/8")	200 / 279 mm (7-7/8" / 11")	200 / 279 mm (7-7/8" / 11")
Vibration Level	2.5 m/s ² or less	2.5 m/s ² or less	2.5 m/s ² or less	2.5 m/s ² or less	2.5 m/s ² or less	2.5 m/s ² or less
Sound Pressure Level	83 dB(A)	83 dB(A)	84 dB(A)	84 dB(A)	83 dB(A)	83 dB(A)
Sound Power Level	94 dB(A)	94 dB(A)	93 dB(A)	93 dB(A)	95 dB(A)	95 dB(A)
Dimensions (L x W x H)	1,230x380x870 - 1,100 mm (48-1/2"x15"x34-1/4" - 43-3/4")	1,330x415x890 - 1,120 mm (52-3/8"x16-3/8"x35" - 44")	1,470x460x955 - 1,230 mm (57-7/8"x18-1/8"x37-5/8" - 48-3/8")	1,465x530x905 - 1,135 mm (57-3/4"x20"-7/8"x35-5/8" - 44-3/4")	1,790x570x950 - 1,165 mm (67"x22"-1/2"x37-3/8" - 45-7/8")	1,790x570x950 - 1,165 mm (70-1/2"x22"-1/2"x37-3/8" - 45-7/8")
Net weight	10.2 kg (22.5 lbs.)	11.6 kg (25.6 lbs.)	14.5 kg (32.0 lbs.)	17.5-19.1 kg (38.6-42.1 lbs.)	27.7-29.2 kg (61.1-64.4 lbs.)	30.5-32.2 kg (67.2-71.0 lbs.)

Standard Equipment: Blade, Wrench, Side Discharge Channel (ELM4620 / ELM4621), Mulch plug (ELM4121 / ELM4620 / ELM4621)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201903