

Can be used as an edger



## Slide type lock-off switch

for safe operation



### Strain relief on main handle

prevents extension cord from disconnecting.



### Adjustable pipe shaft

Simply by touching the button, the length can be adjusted to user's height



**Motor head** rotates 180°



**Dual-cord cutting** 

(using the both ends of a nylon cord 8m in length and 1.65mm in diameter)

### Adjustable loop handle

allows for angle adjustment according to user's height and working posture.

### Easy-to-remove/install spool assembly

Spool assembly can be easily removed by pushing in two locking tabs at once. Additionally, its compact design allows small handed user to push in the





The spool end is metal capped for increased wear resistance.

### **Bump & Feed** cord feeding system

Nylon cord can be fed by tapping the spool end on the ground.

## **String Trimmer**

Double Insulation



### UR3000 300mm (11-3/4")

**Continuous rating Input** 450W **Cutting width** 300mm (11-3/4") No load speed (rpm) Dimensions 1,016~1,256x301x262mm  $(L \times W \times H)$ (40~49-1/2"x11-7/8"x10-3/8") 2.6kg (5.7lbs) Net weight 0.3m (1.0ft) Power supply cord

**Standard Equipment:**Trimmer Head, Shoulder Strap, Safety Goggles

#### Accessories

### **Spool Assembly**

Part No. DA00000001 Spool assembly is designed for user to easily rewind nylon cord, allowing for reuse of spool and spool cover.





# Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan