



Cordless Impact Driver DTD156



Max fastening torque **155N·m**



Work amount
on a single full
battery charge

560 pcs.

Drove 90mm coarse thread
screws into melapi.
with BL1850B (5.0Ah)











Max fastening torque: 155N·m



Belt clip (hook)

	Part No.
Short	346449-3
Long	346317-0








	 DC18RC	 DC18SD
 BL1815N 1.5Ah	15 min	30 min
 BL1820B 2.0Ah	24 min	45 min
 BL1830B 3.0Ah	22 min	60 min
 BL1840B 4.0Ah	36 min	90 min
 BL1850B 5.0Ah	45 min	110 min
 BL1860B 6.0Ah	55 min	130 min

Cordless Impact Driver

DTD156

5

-  Variable Speed
-  Brake
-  Reversing
-  Built-in Job Light
-  Carrying Case

Standard Equipment :

Belt Clip, Battery, Charger

Capacity

Machine Screw: M4 - M8 (5/32" - 5/16")
Standard Bolt: M5 - M14 (3/16" - 9/16")
High Strength Bolt: M5 - M12 (3/16" - 1/2")
Coarse thread (in length): 22 - 125 mm (7/8" - 4-7/8")

Hex Shank

6.35 mm (1/4")

No Load Speed (RPM)

0 - 2,500

Impacts Per Minute (IPM)

0 - 3,000

Max Fastening Torque

155 N·m (11.370 in.lbs.)

Vibration Level

10.0 m/s²

Sound Pressure Level

92 dB(A)

Sound Power Level

103 dB(A)

Dimensions (L x W x H)

w/ BL1815N / BL1820B:
143 x 79 x 223 mm (5-5/8 x 3-1/8 x 8-3/4")

w/ BL1830B / BL1840B / BL1850B / BL1860B:
143 x 79 x 241 mm (5-5/8 x 3-1/8 x 9-1/2")

Net weight

1.3 - 1.6 kg (2.9 - 3.6 lbs.)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202104