



# Cordless Random Orbit Polisher



**DPO600** 150 mm (6")

**DPO500** 125 mm (5")

## High power similar to AC tool



### Rough Polishing



#### Forcible rotation mode

Orbital action with forced rotation of the pad for rough polishing such as scratch removal.



### Fine Polishing



#### Free rotation mode

Orbital action with free rotation of the pad for fine polishing.

# No codes, Less risks of damage for car body



**DPO600**  
150 mm (6")

**DPO500**  
125 mm (5")



Photo : DPO600

**Less damage for car body**

- As the battery is located here, the battery is less likely to hit a car body directly while working.
- Elastomer is covered for less damage on a car body.

**Lock-on button**

**Change knob**  
Selectable 2 rotation mode

Work run time	
Full speed	Finishing mode
about <b>15</b> min	about <b>30</b> min

Battery : BL1850B



Ergonomically designed knob handle provides precision and control in a variety of applications.



Conveniently located speed dial enables operator to match speed to application.



Finishing mode makes it easier to work fine polishing by keeping fixed torque and controlling rotation on heavy duty.

## Accessories

### Side grip



Part No.
198043-5

### Pad

(hook & loop type)



Size	Part No.
100mm	197925-8
125mm	197922-4
150mm	197928-2

### Sponge pad

(hook & loop type)  
(For wax coating)



Size	Part No.
100mm	197893-5
125mm	794558-6
150mm	197894-3

### Wool pad

(hook & loop type)  
(For high gloss polishing)



Size	Part No.
100mm	197896-9
125mm	197897-7
150mm	199424-6

### Felt pad

(hook & loop type)  
(For removing wax)



Size	Part No.
100mm	197895-1
125mm	196152-4
150mm	193288-0

## Cordless Random Orbit Polisher

## DPO600 150 mm (6") / DPO500 125 mm (5")

- Variable Speed
- Constant Speed
- Soft Start
- Hook & Loop
- Carrying Case

	DPO600	DPO500
<b>Pad Size</b>	150 mm (6")	125 mm (5")
<b>Orbits Per Minute (OPM)</b>	Normal mode: 0 - 6,800 Finishing mode: 0 - 5,200	Normal mode: 0 - 6,800 Finishing mode: 0 - 5,200
<b>Strokes Per Minute (SPM)</b>	Normal mode: 0 - 13,600 Finishing mode: 0 - 10,400	Normal mode: 0 - 13,600 Finishing mode: 0 - 10,400
<b>No Load Speed (RPM)</b>	Normal mode: 0 - 780 Finishing mode: 0 - 600	Normal mode: 0 - 780 Finishing mode: 0 - 600
<b>Orbit Diameter</b>	5.5 mm (7/32")	5.5 mm (7/32")
<b>Vibration Level</b>	Polishing: 10.0 m/s <sup>2</sup>	Polishing: 9.5 m/s <sup>2</sup>
<b>Sound Pressure Level</b>	83 dB(A)	82 dB(A)
<b>Sound Power Level</b>	94 dB(A)	93 dB(A)
<b>Dimensions (L x W x H)</b>	530x148x126 mm (20-7/8"x5-7/8"x5")	530x123x134 mm (20-7/8"x4-7/8"x5-1/4")
<b>Net weight</b>	3.1 - 3.6 kg (6.8 - 7.8 lbs.)	3.1 - 3.6 kg (6.8 - 7.8 lbs.)

**Standard Equipment :** Side Grip (country-specific), Pad (country-specific), Hex Wrench

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

**Makita Corporation**

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201904