Two 18V Li-ion batteries can be directly installed on the machine to supply energy to the powerful 36V DC motor drive system.

Thakita

DC18SD

Rear dust exhaust

Dust nozzle is attachable for connecting to vacuum cleaner.



Battery & Charger Time Reference Chart (in Minutes)

DC18RC / DC18RA

DC18SF

Photo:DHS711

	🔊			DC18SE (Automotive)
BL1840	36min.	90min.	1 to 2 batteries	90min.
4.0Ah	Fast Charging	180min.	3 to 4 batteries	
BL1830	22min.	60min.	1 to 2 batteries	60min.
3.0Ah	Fast Charging	120min.	3 to 4 batteries	
BL1815N	15min.	30min.	1 to 2 batteries	30min.
1.5Ah	Fast Charging	60min.	3 to 4 batteries	

Cordless Circular S



Soft grip with non-slip elastomer grip for more control and comfort

Lock-off button is conveniently located and easy to use.

Blower function blows sawdust off the cut line ahead for a better cutting view.

45° stopper

- Positive stop at 45°
- Bevel angle range can be changed from "0°-45°" to "0°-50°".

 Precision bevel adjustment can be made at 45°



Saw	DHS710 / DHS711 190mm (7-1/2") 442		
HALL		DHS710	DHS711
	Max cutting capacity	at 0 degrees : 68.5mm (2-11/16") at 45 degrees : 49mm (1-15/16")	at 0 degrees : 66mm (2-5/8") at 45 degrees : 47.5mm (1-7/8")
	Blade diameter	190mm (7-1/2"")	185mm (7-1/4")
	No load speed (rpm)	4,800	4,800
	Dimensions (L x W x H)	356x217x298mm (14"x8-1/2"x11-3/4")	356x217x298mm (14"x8-1/2"x11-3/4")
2.	Net weight*	4.7kg (10.4bs)	4.6kg (10.1bs)
TTT.			
1	Standard Equipment : Fast Charger, Battery Cartrid	lge, TCT Saw Blade, Hex Wrench, Rip Fence, D	ust Nozzle (for European countries only)

*weight according to EPTA-Procedure 01/2003 Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan PRINTED IN JAPAN BD-BA





As Powerful As Corded Circular Saw

OVERWHELMINGLY HIGH POWER




Cutting Speed

Test material: MDF of 2 x 10 (38mm x 235mm), Bevel angle: 0°



Work Amount on a single full battery charge

Test material: 50mm x 300mm Melapi, Bevel angle: 0°



Note: 1. The test results depend to a great extent on the hardness of materials, etc. 2. The numbers in the charts are relative values when the capacities of Makita BSS611 are indexed at 100. Power source: DHS710 by two 18V-3.0Ah BL1830 BSS611 by 18V-3.0Ah BL1830 Blade used for tests: Saw blade supplied with each model

Max cut depth at 0°



DC circular saws with extra-high power that is as close to the power of AC models as possible.

Lightweight design

- Weighs the same or lighter than our 185mm AC model even with two BL1830 batteries.
- Uses durable but light magnesium die-cast for Blade case and Safety cover.

Well balanced design for easy operation





DHS710









