



Thakita 2 Mode Rotary Hammer






2 Mode Change Lever

Hammering with Rotation

Hammering





:: Slide Chuck




Compact 458mm


HERRICH Tnakita :: No Hammering when Idling **::** Torque Limiter No Hammering while idling When drill bit hits against reinforcements, Reinforcing bar Torque Limiter operates to) D Q (stop the rotation of drill bit,

not compressed unless tool is

because air in the cylinder is pressed against ground. This function ensures machine's long life.



ensuring safety in your work.



:: Rubberized Grip

Provides more comfort and control while minimizing hand fatigue and pain.

:: Aluminum Housing

Provides high quality and toughness.

:: Auto Cut-Out Carbon Brush

When Carbon Brush wears out, it will automatically stop the motor. It protects commutator and indicates time for maintenance.


Comparison of Efficiency

Note: 1. It may differ under some conditions. 2. Numbers in the charts below are relative values when the capacities of Competitor "B" are indexed at 100.


Test conditions: Drilled in concrete with compressive strength of 40N/mm² to a depth of 40mm.

2 Test conditions: Chipped concrete with compressive strength of 40N/mm², and measured the amount of concrete removed.

1 Drilling (Bit diameter: 35mm)



2 Chipping



Rotary Hammer

Torque Limiter

Double Insulation



Carrying Case





HR4002 40mm (1-9/16") 1,050W (10A: North America) **Continuous rating Input** Max. bit dia. 40mm (1-9/16") Max. core bit dia 105mm (4-1/8") Blows per minute 2,500bpm No load speed 680rpm 458mm x 114mm x 256mm (18" x 4-1/2" x 10-1/8") Dimensions (LxWxH) 6.2kg (13.7lbs) Net weight

Power supply cord

Standard Equipment
Depth Gauge, Grip Assembly, Grease Vessel (Tool does not come with bit)

Items of standard equipment and specifications may differ by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan