



Cordless Tower Light ML014G

Satisfy Professional's Needs



XGT
40V **Li-ion**
max


18V
LITHIUM-ION

**Max. luminous
flux 15,000 lm**



For lighting at worksites
without a power source

Continuous use (approx)	at Min luminous flux	at Max luminous flux
with BL4080F + BL18120	48 h	3.6 h
with BL4080F	28 h	2 h
with BL18120	20 h	1.6 h



XGT
40V^{Li-ion}max
18V^{Li-ion}LITHIUM-ION
Delivers wide-area illumination from a high position


Adjustable light angle

The light angle is easily adjustable to suit your application, providing optimal illumination.


The light head rotates 180° Vertically




Horizontally



Light base rotates 180° Vertically



Illumination range (Single-sided)



Forward Direction about 8 m

With soft-start illumination



Downward



Single-sided



360°



Excellent portability

Lightweight Body & Integrated Tripod

Lightweight
9.5 kg (tool only)

Height (folded)
about 1 m



Manually adjustable height

The setup height of light head can be adjusted from 1,085 to 2,430mm.



Easy tripod setup by slide handle



Brightness adjustment dial

(Stepless: 1,100 - 15,000lm)



Power button

Desired battery can be discharged first. (by pressing and holding the power button).

Battery capacity warning lamp

Battery: 40Vmax/18V LXT



Upto two battery can be installed:
• Only one XGT or 18V LXT
• Two; One XGT and One 18V LXT in parallel connection

Anti-Tipping Design

To prevent accidental tipping, the tripod can be secured to ground with hook stakes. (Use commercially available hook stakes.)



Accessories

Shoulder belt
Part No. TD00000002



Charging Time

40V^{Li-ion}max	Fast Charging		18V^{Li-ion}LITHIUM-ION	Fast Charging	
	DC40RA	DC40RC		DC18RC	DC18SD
BL4020 2.0Ah	22 min	30 min	BL1815N 1.5Ah	15 min	30 min
BL4025 2.5Ah	28 min	38 min	BL1820B 2.0Ah	24 min	45 min
BL4040/F 4.0Ah	45 min	67 min	BL1830B 3.0Ah	22 min	60 min
BL4050F 5.0Ah	50 min	85 min	BL1840B 4.0Ah	36 min	90 min
BL4080F/H 8.0Ah	76 min	170 min	BL1850B 5.0Ah	45 min	110 min
			BL1860B 6.0Ah	55 min	130 min
			BL1890 9.0Ah	85 min	200 min
			BL18120 12.0Ah	120 min	265 min
Compatible with charger DCB18WA only					
18V^{Li-ion}LXT BASIC	BLB182 2.0Ah	90 min			

Charge the LXT batteries with the LXT battery chargers and the LXT BASIC battery with the LXT BASIC battery charger.

Cordless Tower Light

ML014G

Soft Start

*1 Other conditions (at Max luminous flux - at Min luminous flux)

Standard Equipment:
Shoulder belt

Luminous flux	1,100 - 15,000 lm
Illuminance	at 1 m from the light source: 400 - 5,000 lx
Continuous use ^{*1} (Battery)	2.0 - 28 h (BL4080F)
Continuous use ^{*1} (Battery)	3.6 - 48 h (BL4080F and BL18120)
Max setup height	2,430 mm (8 ft)
Dimensions (L x W x H)	Folded position: 290 x 265 x 1,035 mm (11-3/8 x 10-3/8 x 40-3/4")
	Extended position: 780 x 680 x 1,085 - 2,430 mm (30-3/4 x 26-3/4 x 42-3/4 - 95-1/2")
Net weight (with Battery)	12.8 kg (28.2 lbs.) (BL4080F and BL18120)

The specifications herein are subject to change without notice.
Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202604